

技术咨询和询价：010-68940148



FEATURES

High Resolution: 0.01μΩ
Wide current measurement range from 5A to 220A
Standard resistor to conduct accuracy test
Handheld device, rugged and easy-to-operate
High stability with open circuit and overheating protection

SPECIFICATIONS

Function	Contact resistance tests of high-voltage switches and circuit breakers; connection resistance tests of metallic welding components; circuit resistance tests of conductors; precise low resistance tests.		
Power	Built-in 12.6V 9000mAh rechargeable lithium battery		
Measurement Method	4-wire measurement		
Charger	12.6V/2A		
Display	5.6-inch industrial LCD with high-brightness color		
Test Interface	I+, I-, U+, U-		
Output Current	≤5A, 10A, 30A, 50A, 80A, 100A, 200A, 220A		
	Step Current: 2.5A, up to 59 current gears.		
Measurement Range	≤5A: 1μΩ~3500mΩ		
	10A: 0.1μΩ~200mΩ		
	30A: 0.1μΩ~20mΩ		
	50A: 0.01μΩ~15mΩ		
	80A: 0.01μΩ~10mΩ		
	100A: 0.01μΩ~5mΩ		
	200A: 0.01μΩ~600uΩ		
	220A: 0.01μΩ~500uΩ		
Resolution	0.01μΩ		
Accuracy	30A~220A:	0.01μΩ~20mΩ	0.5%±1μΩ
	5A~10A:	0.1μΩ~200mΩ	1%±5dgt
	≤5A:	1μΩ~3.5Ω	1%±5dgt
Measurement Time	≤100A: fast mode(recommend)、10s, 20s, 30s, 40s、50s, 60s >100A: fast mode		
Printer	Press the print button to print the test results		
Data Storage	After the completion of the test, the data is automatically and cyclically saved with up to 999 sets of data stored.		
Size of the instrument	L188mm×W85mm×H312mm		

Size of Outer Package	Appro L550mm×W420mm×H215mm
Test Leads	Weight of the instrument: appro 2.2kg
	Total Weight: appro 9.3kg
Test Leads	Standard Length: 3m (5m is optional)
	Connecting the test leads to the current port and voltage port with a resistance of less than 10mΩ
Data Delete	Select Format Memory in the setting interface to delete all data
Data Query	Enter the Data Query interface, press the up, down, left, or right keys to browse the stored data
Data Export	Bluetooth connection, Android App to export Excel files
Cloud Service	Android APP, Bluetooth connection; upload on-site pictures and data, generate test report and graph, share test equipment, and view data simultaneously by multiple people
Automatic shut-down	The battery will automatically shut down if no operation within 15 minutes after power on
Battery Voltage	When the symbol“  ”is displayed on the upper right corner of the instrument, it means that the battery power is exhausted, and it will automatically shut down. Please charge it in time.
Backlight	High, medium, and low brightness
Working Current	The current is 230mA in a non-test state
	The current can be set in the test state
Circuit Protection	Open circuit protection, overheat protection
Overcurrent Protection	By temperature monitoring
Working Temperature and Humidity	-10℃～50℃; below 90%RH, no condensation
Storage Temperature and Humidity	-10℃～60℃; below 70%RH
Charging Voltage	12.6V
Safety Standard	IEC61010-1, IEC61326-1; IEC61000-3-2;CAT III 600V、Pollution Level 2, DL/T967-2005Verification regulation of loop resistance tester and DC resistance high-speed tester.

Package Includes

- Carrying Case
- Test Leads Set (Black & Red – 3m)
- Alligator Clip Set
- Self Testing Resistor
- Printer Set (Charger & Paper)
- Device Charger
- User Manual
- Test Report (Optional)



Ordering Info.

- DOM220..... Micro Ohmmeter Kit
- P3051303..... Standard 3 Meter Test Leads Kit
- P3052301..... Device Charger
- P3052302..... 12.6V 9000mAh Rechargeable Lithium Battery
- P3052303..... Printer Kit